## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 2559

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	DC Female		
(or other electric interface)	connector		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

**Product parameters** 

Flouder parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
	mption in on- 100 h), rounded 1st integer	3	Energy efficiency class	E			
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode p expressed in W	oower (P <sub>on</sub> ),	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer	Height	4	Spectral power	See image			
dimensions	Width	8	distribution in the	in last page			
without	Depth	500	1	Dago 1 / 2			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,440			
		coordinates (x and y)	0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	1,00			
the lumen maintenance factor	0,96					
(a)		1				

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

