


INSTALLATION INSTRUCTION

Model: VT-1182

LED STEP/WALL LIGHT OURDOOR



LED STEP/WALL LIGHT OURDOOR

INTRODUCTION

Thank you for selecting and buying V-TAC LED STEP/WALL LIGHT OURDOOR. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any other query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best.

TECHNICAL PARAMETERS

	lamp	warm white	natural white	cool white
performance parameter	lumen (lm)	190 lm	200 lm	210 lm
	color temperature (K)	3000K	4000K	6400K
	CRI	≥80		
	type of LED	SMD LED		
	beam angle	90		
	decay rate (%)	less than 3% within 1000 working hours		
	total power (W)	3-4W		
	lifespan (hrs)	≥30000hrs		
	high voltage testing	1750vac/1min		
	lighting efficiency	100Lm/W		
LED parameter	chip quantity	10PCS		
	series-parallel way	5C2B		
	voltage	43-47V		
	current	50mA		
driver parameter	input parameter	100~240VAC, 50/60Hz		
	power factor	0.5		
	output parameter	50mA 40-90v		
structure parameter	material	PC		
	dimension	166*94mm		
	cut-out	/		
	protection class	I级		
	IP	IP65		
environment parameter	application	hotel, home-lighting, recreation place, supermarket, office building		
	operating temperature	-25℃ ~ 50℃, 10% ~ 90% R.H.		
	storage temperature	-30℃ ~ 85℃, 0% ~ 95% R.H.		
packing	Qty/Ctn	carton size	N, W	G, H